

AMENDMENTS TO THE CLAIMS

The claims in this listing will replace all prior versions, and listings, of claims in the application.

Listing of Claims

1. (Currently Amended). A binocular telescope with a photographing function, said binocular telescope having a pair of observation optical systems with an adjustable interpupillary distance, and a photographing optical system, said pair of observation optical systems being utilized as a focusing device for said photographing optical system, said binocular telescope comprising:

a first focusing mechanism that focuses said pair of observation optical systems so as to observe an object through said pair of observation optical systems;

a second focusing mechanism that focuses said photographing optical system so as to photograph said object through said photographing optical system;

an association mechanism that associates said first and second focusing mechanisms with each other such that said pair of observation optical systems and said photographing optical system are always kept in a focused state;

a pair of reticle elements on which reticles are formed, and which are provided in each observation optical system of said pair of observation optical systems for focusing said pair of observation optical systems with a predetermined dioptric power during an operation of said first and second focusing mechanisms, each of said pair of reticle elements being arranged at an in-focus position of an

P23759.A10

objective lens system of said observation optical system, a position of an ocular lens system of said observation optical system being adjustable relative to the position of said reticle element so as to adjust the dioptric power; and

an interpupillary distance adjuster that adjusts the distance between the optical axes of said pair of observation optical systems;

wherein, when the optical axes of said pair of observation optical systems are made completely coincident with the interpupillary distance of the user by using said interpupillary distance adjuster so that reticle images of said pair of reticle elements are fused, the fused reticle images are geometrically non-coordinate with each other and form a cross.

2-3. (Canceled).

4. (Original). A binocular telescope according to claim 1, wherein each of said reticles comprises at least one line segment.

5. (Original). A binocular telescope according to claim 4, wherein each of said reticles comprises at least two line segments, which extend radially from the optical axis of the corresponding observation optical system.

6. (Original). A binocular telescope according to claim 4, wherein each of said reticles comprises at least two line segments, which extend radially from a

P23759.A10

circular area encircling the optical axis of the corresponding observation optical system.

7. (Original). A binocular telescope according to claim 1, wherein each of said reticles comprises at least one geometrical figure.

8. (Previously Presented). A binocular telescope according to claim 7, wherein each of said reticles comprises a geometrical figure, the center of which is coincident with the optical axis of the corresponding observation optical system, said geometrical figures being similar figures.

9. (Original). A binocular telescope according to claim 1, wherein each of said reticles comprises at least one dot.

10. (Previously Presented). A binocular telescope according to claim 9, wherein each of said reticles comprises a plurality of dots which are arranged on a plane perpendicular to the optical axis of the corresponding observation optical system, said plurality of dots being aligned on line segments which are symmetrical with respect to a straight line on said plane.

11. (Previously Presented). A binocular telescope according to claim 9, wherein one of said reticles comprises a dot which is aligned on the optical axis of

P23759.A10

the corresponding observation optical system, and the other of said reticles comprises a plurality of dots which are arranged on a plane perpendicular to the optical axis of the corresponding observation optical system, and arranged around the optical axis.

12. (Previously Presented). A binocular telescope according to claim 1, wherein said association mechanism comprises a rotary wheel member having a manually operated rotary wheel; each of said pair of observation optical systems comprises two optical system elements that are movable along the optical axis of said observation optical system to focus said observation optical system; said first focusing mechanism comprises a first movement-conversion mechanism for converting a rotational movement of said rotary wheel member into a relative back-and-forth movement of said two optical system elements; said photographing optical system is movable relative to an imaging plane along the optical axis of said photographing optical system to focus said photographing optical system; and said second focusing mechanism comprises a second movement-conversion mechanism for converting a rotational movement of said rotary wheel member into a back-and-forth movement of said photographing optical system elements relative to said imaging plane.

13. (Previously Presented). A binocular telescope according to claim 12, wherein said rotary wheel member comprises a rotary wheel cylinder in which a

P23759.A10

lens barrel is housed so as to be movable along the central axis of said rotary wheel cylinder; said photographing optical system is housed in said lens barrel; said second movement-conversion mechanism comprises a first cam groove formed in one of said rotary wheel cylinder and said lens barrel, and a first cam follower formed in the other of said rotary wheel cylinder and said lens barrel; and said first cam groove is configured such that a rotational movement of said rotary wheel cylinder is converted into a back-and-forth movement of said lens barrel along the central axis of said rotary wheel cylinder.

14. (Original). A binocular telescope according to claim 13, wherein said first movement-conversion mechanism comprises a second cam groove formed on an outer surface of said rotary wheel cylinder, an annular member that has a second cam follower engaged with said first cam groove and that is attached on an outer surface of said rotary wheel cylinder to move along the central axis of said rotary wheel cylinder, and a movement transmission mechanism that transmits the movement of said annular member to one of said two optical system elements of each of said pair of observation optical systems.

15. (Previously Presented). A binocular telescope according to claim 12, wherein said pair of observation optical systems are mounted on an optical system mount plate that comprises first and second plates that are movable relative to each other, one of said pair of observation optical systems is on said first plate, and

P23759.A10

the other of said pair of observation optical systems is on said second plate, so that the distance between the optical axes of said pair of observation optical systems is adjusted by changing the relative positions of said first and second plates.

16. (Original). A binocular telescope according to claim 15, wherein said first and second plates are linearly moved relative to each other, so that the optical axes of said pair of observation optical systems are moved in a predetermined plane, whereby the distance between the optical axes of said pair of observation optical systems is changed.

17-29. (Canceled).

30. (Previously Presented). A binocular telescope according to claim 1, wherein a shape of a reticle image of a first reticle element of said pair of reticle elements is different than a shape of a reticle image of a second reticle element of said pair of reticle elements.

31-33. (Canceled).